


SPECIFICATIONS

Size	Metric	British
Max. Working Height A	13.80m	45ft 3in
Max. Platform Height B	11.80m	38ft 9in
Overall Length C	2.48m	8ft 2in
Overall Width D	1.19m	3ft 11in
Overall Height(Rails Up) E	2.62m	8ft 7in
Overall Height(Rails Down) F	2.09m	6ft 10in
Platform Size(Length×Width)	2.27m×1.12m	7ft 5in×3ft 8in
Platform Extension Size G	0.90m	2ft 11in
Ground Clearance(Stowed/Raised)	0.10m/0.019m	4in/1in
Wheelbase H	1.87m	6ft 2in
Turning Radius(Inside/Outside)	0m/2.20m	0in/7ft 3in
Tyres	φ381×127mm	φ381×127mm

Performance		
S.W.L	320kg	705lb
S.W.L On Extension	113kg	249lb
Max. Occupants	3	3
Gradeability	25%	25%
Travel Speed(Stowed)	5.0km/h	3.10mph
Travel Speed(Raised)	0.8km/h	0.50mph
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Up/Down Speed	55/40sec	55/40sec

Weight		
Overall Weight(Lead-acid Battery)	2990kg	6591lb
Overall Weight(Lithium Battery)	2900kg	6393lb

Power		
Hydraulic Tank	20L	5.3gal
Battery	24V/240Ah	24V/240Ah
Charger	24V/30A	24V/30A
Driving Motor	2×24VAC/0.87kW	2×24VAC/0.87kW
Lifting Motor	24VAC/3.50kW	24VAC/3.50kW



FEATURES

Standard Items

- Proportional Joystick Controls
- Self-Locking Gates
- One-Way Platform Extension Deck
- Drivable At Full Height
- Non-Marking Tyres
- Two-Wheel Drive
- Two-Wheel Steering
- Automatic Braking System
- Emergency Descent System
- Tubing Explosion-Proof System
- Onboard Fault Diagnostic System
- Tilt Alarm
- Motion Alarm
- Horn
- Hour Meter
- Safety Arm For Troubleshooting
- Standard Transport Forklift Holes
- Charging Protection System
- Flashing LED Beacon
- Foldable Guard Rails
- Automatic Pothole Protection
- Drive Enable
- Charging Indicator
- Manual Brake Release
- Lanyard Attachment Point
- Tie-Down And Lifting Points
- Platform Load Sense System
- Emergency Stop Button



ZHEJIANG DINGLI MACHINERY CO., LTD.

Address: No.188 Qihang Road, Deqing, Zhejiang P.R.C 313219

Telephone: +86(572)8681688

E-Mail: export@cndingli.com

<https://en.cndingli.com>